



X3G FASTGOUGE 800 **POWERFUL,** **ROBUST** **AND SIMPLE**

X3G offers a powerful, robust and simple solution for heavy-duty carbon arc gouging applications. 800 amps of power and a 50% duty cycle ensure maximum productivity and efficiency for those tough and challenging jobs.



Powerful and extremely reliable

X3G FastGouge delivers 800 amps and 50% duty cycle.

Simple to operate

Select Gouging or MMA, set to the required power and start working.

Designed for tough conditions

Robust construction and dust filters fitted as standard, protect the machine against real-life conditions.

Feature	X3 FastGouge
Connection voltage 3~, 50/60 Hz	380...415 V, +-10 %
Rated power at max. current 50 % ED	45 kVA
Output 50 % ED	800 A / 44 V
Output 100% ED	600 A / 44 V
Fuse	63 A delayed
Welding range	20 A / 20 V...800 A / 44 V
Connection cable	H07RN-F (16 mm)
Open circuit voltage	100 V
Power ratio at 100 % ED	0.87
Efficiency at 100 % ED	0.91
Gouging carbon, maximum diameter mm	13
Operating temperature range	-20...+40 °C
Storage temperature range	-40...+60 °C
EMC class	A
Degree of protection	IP23
External dimensions L x W x H	730 × 268 × 796 mm
Weight without accessories	73 kg
Product code	X3G800



ACCESSORIES

GT4000 Gouging Torch and Cables
X3GT2 Trolley



DESIGNED FOR BADASS WELDERS

Scan for more info

